

Multiple Talent
for Industry and Craftsmen

NEW!

WIWA RS-1

The WIWA RS-1 is a robust, versatile, high performance Paint Spray Unit for Airless and Air Combi Spraying.



WIWA RS-1/F
Order No. 0650555

Technical Data	
Max. output at free flow	4,2 ltr./min
Avg. air consumption at 30 cycles/min and 8 bar air inlet pressure	240 ltr./min
Pressure ratio	33:1
Max. operating pressure	264 bar
Output per cycle	27 ccm
Max. air inlet pressure	8 bar
Weight RS-1/F - RS-1/G	approx 30 kg / 18 kg

Wilhelm Wagner GmbH & Co. KG
Gewerbestraße 1-3 • D-35633 Lahnau,
E-mail: info@wiwa.de • www.wiwa.de
Tel.: +49 (0)64 41-6 09-0 • Fax: +49 (0)64 41-6 09-50

Advantages:

- extremely low spray fog
- robust and easy-to-carry for efficient lacquering
- fast change of colours, minimum need of cleaning agent
- ideally suited for small amounts of paint
- high material savings
- all conventional lacquers and paints can be processed
- fast and easy maintenance
- top quality of lacquering with finest atomisation
- special sealing, no piston packing
- all parts in contact with the material are made of stainless steel (VA)

Fields of application

Main application fields are carpentry shops, furniture industry, paint and finishing shops, machine and car industry

Material to be sprayed

Primer, sprayable paint and lacquer, plural component paints, thick-coat varnish, etc.



WIWA RS-1/G
Order No. 0649148